

HI-07 / Display

Hi-07 is designed around the retro-fit GU10 LED lamp, connecting directly to the 240V supply so is recommended when remote drivers cannot be accommodated. The handsome spun aluminium shade delivers precisely controlled lighting, ideal for illuminating an artwork, highlighting interior details or general downlighting when mounted to the ceiling. Available with a variety of lamp options, from museum-grade CRI 97 to more budget orientated LEDs.

product details

Description:	Classic display spotlight for museum, gallery, retail and residential interior applications
Mounting:	Direct mount to a panel, wall or ceiling
Material:	Aluminium/steel/brass/acrylic
Weight:	0.5kg
Power supply:	240V
Certification:	Luminaire - CE, LED driver - CE (UL Listed, CCC etc upon request)

technical specification

LED operating current:	30mA
LED operating voltage:	240V
Total system power:	5.5W
Control:	Non-dimmable / Phase dimmable
Lifetime (light source):	40,000hrs (lamp)

optical specification

Total lumen output:	400lm (4000K)
Luminous efficacy:	73lm/W (4000K)
Light output ratio:	100% (lamp)
Beam angle (FWHM):	25° / 36°
Colour temperature:	2700K / 3000K / 4000K
CRI:	97
MacAdam step:	3

finishes

Powder coated:	Matt silver / matt black / satin black RAL 9005 / white RAL9016 / bronze / other finishes on request
Plated:	Brushed stainless steel / brushed chrome / polished chrome / polished brass / brushed brass / antique bronze / other finishes on request

fixings

Panel mount:	W1 - Ø20mm surface washer with M10 allthread W1/E3 - Ø20mm surface washer with M10 allthread and Ø15mm collar (non-standard heights)
Surface mount:	F1 - Ø40mm fixing plate F2 - Ø75mm fixing plate for wall mounting onto brick / plasterboard S plate - Ø75mm x 26mm plate with 240V connection block
Track mount:	For standard single or three-circuit 240V track

