

## Twig / Display

Twig/Display excels at general purpose cabinet lighting, and continues to be a popular choice for museums and jewellery retailers both high street and high-end. Its 120° beam angle is particularly effective when a wide spread of light is required to illuminate a range of artefacts or jewels. High colour rendering (90CRI) LED, selection of colour temperatures.

### product details

Description:	Discreet and superslim display light for museum, gallery and retail applications
Mounting:	Direct mount to a panel, wall or ceiling
Material:	Aluminium/steel/brass/acrylic
Weight:	0,15kg (295mm)
Power supply:	Remote Class II SELV LED driver
Certification:	Luminaire - CE, LED driver - CE (UL Listed, CCC etc upon request)

### technical specification

LED operating current:	350mA constant current
LED operating voltage:	9V DC
Total system power:	3.1W (excl driver)
Control:	Non-dimmable / DALI / 1-10V / Phase
Lifetime:	50,000hrs

### optical specification

Total lumen output:	250lm (4000K)
Luminous efficacy:	80lm/W (@ 350mA, 4000°K, excl driver)
Beam angle (FWHM):	120°
Colour temperature:	2700K / 3000K / 3500K / 4000K / 5000K
CRI:	90
MacAdam step:	3

### finishes

**Powder coated:** Matt silver / matt black / satin black RAL 9005 / white RAL9016 / bronze / other finishes on request

**Plated:** Brushed stainless steel / brushed chrome / polished chrome / polished brass / brushed brass / antique bronze / other finishes on request

### fixings

Panel mount:	W1 - Ø20mm surface washer with M10 allthread and locknut (standard height) W1/E2 - Ø20mm surface washer with M10 allthread and locknut, Ø15mm collar (non-standard heights)
Surface mount:	F1 - Ø40mm fixing plate F3 - 40mm x 20mm rectangular surface fixing
Stem options:	Tall - Ø12mm stem. Specify total height required including spotlight head. Wall - No stem, for direct mounting to cabinet

